QUELL

Fire Extinguisher 4.5kg (6A:60B:E)



Overview

Quell's fire extinguishers provide a range of solutions for:

- Homes
- Garages
- Marine
- Automotive
- Industrial

The Quell 4.5kg fire extinguisher is Australian Standard certified and comes with a 5 year warranty.

Shopping for a fire extinguisher has never been easier with Quell's easy application-based packaging, giving consumers peace of mind that they are choosing the right product.

Features & Benefits

- Australian Standard certified to AS1841.5
- Stainless steel polyester powder coated handle and trigger
- · Mild steel polyester powder coated cylinder
- ABE (mono-ammonium phosphate) dry chemical powder
- Rated for use on Class A, Class B and Class E fires
- Ready for use pressure indicator
- Forged brass valve
- · Powder coated steel wall bracket

Technical Specifications


Model Number	Q136178	
Туре	DCP (Stored pressure)	
Capacity	4.5 kg (Tol: ±2%)	
Contents	ABE40 Powder	
Rating	6A:60B:E	
Test Pressure	2.5 MPa	
Operating Pressure	1500 kPa	
Nominal Mass	7.50 kg	
Discharge Time	17 - 21 s	
Nozzle Orifice	4.5 mm	
Service Temperature	-5°C to 65°C	


NOTE: Nominal mass and discharge times listed are approximate. Slight variations may occur.

Ordering Information

Q136178	Quell 4.5 kg extinguisher industrial
	with metal service tag (6A:60B:E)

Product Dimensions





Compatibility Chart

	Class A	Class B	Class E
Which Fire Extinguisher	Combustible materials e.g.	Flammable liquids e.g.	Electrical equipment e.g.
do I use for which fire?	Wood, Paper,	Petrol, Paint or	Appliances,
	Fabric	Turpentine	Computers, Phones
1 kg 1A:10B:E	√	✓	√
1 kg 1A:20B:E	✓	✓	✓
1.5 kg 2A:30B:E	✓	\checkmark	✓
0.01 0.1 10.0 5			
2.3 kg 2A:40B:E	V	▼	~
4L 2A	✓		
4.5 kg 6A:60B:E	\checkmark	\checkmark	✓
9.0 kg 6A:80B:E	√	\checkmark	√

Service Requirements

Service in accordance with Australian Standard AS1851.

Additional AS1851 Service Requirements:

- Replace Dry Chemical Powder every five (5) years
- The recommended location for stamping the cylinder pressure test date is on the neck ring of the cylinder, consisting of figures not less than 3mm in height and shall as a minimum be of the form MM/YY, or MM/YYYY.

~183

Contact

For further information on the full range of Quell® products, visit our website www.quell.com.au

Kidde Australia Pty Ltd ABN 68 006 252 428 Building F, Unit 1B, 3-29 Birnie Avenue Lidcombe NSW 2141