



 +  **MAINS
POWERED**
+ BATTERY
BACK-UP

240V AC

Q5000 Wireless Interconnect Photoelectric Smoke Alarm



Overview

The Quell Q5000 240V Wireless Interconnect Photoelectric smoke alarm, allows the interconnection of up to 32 Q5000 series alarms using innovative Radio Frequency technology. With a 100m direct line of sight range, all interconnected smoke alarms sound when one smoke alarm detects smoke, giving you and your loved ones early notification to evacuate.

The Q5000 240V has two levels of internal screening that minimises insect and dust contamination in the alarm, along with a safety lock that ensures it remains tamper-proof once installed.

What is Included

- 240V Smoke alarm with sealed battery
- Separate mounting base
- Screws and plugs fixings
- Manual

Features & Benefits



Interconnectable

Wirelessly interconnects up to 32 Q5000 series devices (no internet or wiring required).



Reduced Nuisance Alarms

Multi-layer insect screen minimises insect and dust contamination.



Sealed Battery

10 year long life sealed backup battery.



End of Battery-life Notification

30-day low battery alert.



Operating Temp: 0°C to 40°C

Operating Humidity: Up to 93% RH non-condensing



10 year warranty.

Protecting what matters most

Technical Specifications

Product Code	140052
Model Number	Q5000ACS-WB
Diameter	98 mm
Profile	53 mm
Smoke Alarm Type	240V mains powered photoelectric smoke alarm with wireless interlink
Usage	Suitable for ceiling or wall mounting in residential properties
Operation AC/DC	AC
Battery Type	Non-replaceable 10 year battery (pack of 2 CR123A Lithium batteries)
Power Consumption	Supply Voltage: 230 VAC Monitoring Mode Current: 0.030 mA Battery Backup: Up to 2 years of operation when disconnected from the 240V mains supply.
Battery Life	Minimum 10 year life in normal operating condition (Based on a weekly testing)
Range	Minimum 100 m in open field. Range depends on the building materials and will need to be tested in each individual case
Sound	Audible indicator of minimum 85 dB @ 3 metres
Sound Pattern	Fire alarm mode is indicated by a series of three successive tones
Visible Indicators	A red LED is used to indicate the following; • Fire alarm mode is indicated by a flash every 0.5 seconds • Smoke sensed speed up in chamber is indicated by a flash every 2 seconds when the smoke level is at the alarm threshold • Normal operation is indicated by a flash every 48 seconds
Product Weight (GR)	Base alarm weight (excluding screws, plugs and mounting ring): 205 g
Operating Temperature	Not recommended for operation below 0°C or above 40°C
Operating Humidity	Up to 93% RH non-condensing
Compatibility	Q5000DCS-WCB / Q5000DCS-WCLH / Q5500DCS / Q5000ACS-WB
Certification	AS3786:2023

Ordering Information

140052	Quell 240V Wireless Interconnect Photoelectric smoke alarm with 10yr sealed battery backup
--------	--

Distributed by:

Contact

For further information on the full range of Quell® products, visit our website www.quell.com.au

Kidde Australia Pty Ltd
ABN 68 006 252 428
Building F, Unit 1B, 3-29 Birnie Avenue
Lidcombe NSW 2141

Quell® is a registered trademark of Kidde Australia Pty Ltd.
©2026 Kidde. All rights reserved.

QUELL_140052_DS_SEPT2026